



01642260

SKT 340/16 E^{IZ}

Where to buy ☑

Product specifications

Characteristic	Value
Case	B8
Chip Technology	Thyristor
Current (A)	340 A
Dimensions (LLxBBxHH) mm	D42x14
Features	 Hermetic metal case with ceramic insulator Capsule package for double sided cooling Shallow design with single sided cooling International standard case Off-state and reverse voltages up to 1800 V Amplifying gate
Housing	Capsule
Part Number	01642260
Product Line	Capsule
Product Status	In production new
Product Type	SKT 340/16 E
Surge Current (A)	5200 A
Technology	Thyristor
Typical Applications	• DC motor control (e. g. for machine tools) • Controlled rectifiers (e. g. for battery charging) • AC controllers (e. g. for temperature control) • Recommended snubber network e.g. for Vvrms \leq 400 V: R = 33 Ω /32 W, C = 0,47 μ F
Voltage (V)	1600 V

For the most current information and other product assets, please use this link to visit the product page on Semikron Danfoss ☑

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material changes being necessary in specifications already agreed. All trademarks in this material changes being necessary in specifications already agreed.	